




CLEVERCITI SIGN WITH FRONT SERVICE

## Multi-Purpose Dynamic LED Messaging



The Cleverciti Sign with Front Service is a fully dynamic, high resolution LED messaging sign for all on- and off-street parking areas. It offers intelligent navigation and real-time parking guidance information to users as live data changes. The CleverCiti Sign is also the perfect for special event messaging, emergency alerts, and advertising.

Front service panels provide an enhanced level of installation and maintenance convenience, with simple access for maintenance or panel exchange. Managed remotely by Cleverciti Cockpit, the Cleverciti Sign with Front Service is available in a wide range of sizes.

- Accurate, real-time parking guidance
- Fully digital, high-resolution displays
- Dynamic message signage (DMS)
- Optimal viewing angles
- Character heights for any application
- Optimal brightness for visibility
- Navigation to destinations
- Front panel access for convenient maintenance
- Managed and monitored remotely by Cleverciti Cockpit
- Easy installation on existing infrastructure

# Technical Specifications

## DISPLAY PARAMETERS

**STANDARD MOUNTING BRACKET:** Center-mounted on single pole (diameter 90-220mm). Custom brackets available by request.

**MINIMUM SIZE:** 75 cm x 75 cm (29.5 in x 29.5 in)

**ADDITIONAL SIZE STEPS POSSIBLE:** +25 cm in height or width (9.84 in)

**ADDITIONAL SPACE FOR FRAME:** 0 cm on all sides (frameless design)

**BRIGHTNESS:** 6000 nits (cd/m<sup>2</sup>)

**BEST VIEWING DISTANCE:** ≥7 m

**VIEWING ANGLE:** 140 degrees (horizontal and vertical)

**DISPLAY COLORS:** 4.4 Trillion Colors

**GRAY GRADE:** 14 (bit)

**BRIGHTNESS ADJUSTED:** 100 grades by software or automatically by sensor

**OPERATION POWER:** AC 100 – 240 V 50-60 Hz Switchable

**AVERAGE POWER CONSUMPTION:** 200 watts per m<sup>2</sup>


**PEAK POWER CONSUMPTION:** 600 watts per m<sup>2</sup> (all white, full brightness)

**INRUSH CURRENT (TYP):** Cold start 40A at 230 VAC

**FRONT SERVICE ACCESS:** Yes (enables easy maintenance)

**CABINET MATERIAL:** Aluminum

**WEIGHT:** Approx. 35kg per square meter + 33 kg per sign for installation hardware (exact weight for specific sign size available upon request)



## MODULE PARAMETERS

**MODULE TYPE:** LED

**RESOLUTION/PIXEL PITCH:** 0.481 cm (0.19 in)

**PIXEL CONFIGURATION:** SMD192

**DENSITY:** 43,264 pixels/m<sup>2</sup>

**MODULE RESOLUTION:** L: 52 pixels; H: 52 pixels

**MODULE DIMENSION:** L: 25 cm; H: 25 cm; D: 1.8 cm  
(L: 9.8 in; H: 9.8 in; D: 0.71 in)

**DRIVING MODE:** Constant current, 1/6 duty

**MODULE MASK:** Pure black mask – high contrast screen

## RELIABILITY

**WORKING TEMPERATURE:** -20~+60 degrees C

**WORKING HUMIDITY:** 10%-90% RH

**LIFETIME:** 100,000 Hours

**PROTECTION GRADE:** IP65 (front), IP54 (rear)

**OUT-OF-CONTROL PIXEL RATE:** ≤0.01 %

The Cleverciti Sign is available in the following standard sizes. Custom sizing is also available upon request. The number of lines is based on a standard line of text being up to 18 cm high. As fully digital signs, in addition to lines of text, the sign is also capable of showing visual maps and images – custom template design is available upon request.

2 LINES: 125 cm x 50 cm (49.2 in x 19.7 in) (W x H)

4 LINES: 125 cm x 100 cm (49.2 in x 39.4 in) (W x H)

6 LINES: 125 cm x 150 cm (49.2 in x 59 in) (W x H)

3 LINES: 125 cm x 75 cm (49.2 in x 29.5 in) (W x H)

5 LINES: 125 cm x 125 cm (49.2 in x 49.2 in) (W x H)

8 LINES: 125 cm x 200 cm (49.2 in x 78.4 in) (W x H)

Cleverciti is a registered trademark of Cleverciti Systems GmbH.  
All rights reserved.

CLEVERCITI SYSTEMS GMBH  
GLOBAL HEADQUARTERS

Munich Office  
Hofmannstrasse 54  
81379 Munich, Germany  
Tel: +49 89 78576736-23

CLEVERCITI SYSTEMS CORP.  
NORTH AMERICAN OFFICES

Atlanta Office  
8000 Avalon Blvd. Suite 100  
Alpharetta, Ga. 30009  
Tel: (331) 218-7323

www.cleverciti.com  
info@cleverciti.com